

2002

**Virginia Department of Transportation
Daily Traffic Volume Estimates**

Jurisdiction Report

24

Cumberland County

Prepared By

**Virginia Department of Transportation
Mobility Management Division**

In Cooperation With

**U.S. Department of Transportation
Federal Highway Administration**

Virginia Department of Transportation
Mobility Management Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management's Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT’s Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

Peak Hour: The estimate of the traffic volume for the 30th highest traffic volume occurring in a one-year period divided by the AADT for the same one-year period.

QK: Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During 12 Months of Continuous Traffic Data
- B Factor based on 30th Highest Hour Observed During Less than 12 Months of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of 30th Highest Hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the Peak Hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

- North
 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
-  US Route
-  Virginia State Route
-  Secondary Route

Special Routes

- Bus
 Bus - Business Route
Bypas - Bypass Route
Truck - Truck Route
- ALT
 ALT - Alternate Route
Wve - Wve Route connector
-  P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
-  The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Cumberland Maintenance Area

Route	Length	AADT	QA	Year
Cumberland County				
From: US 60				
(13)	7.19	780	F	2002
To: Powhatan County Line				
From: NCL Farmville				
(45)	3.54	5200	F	2002
To: 24-636 Raines Tavern				
(45)	4.66	3900	F	2002
To: 24-634				
(45)	5.82	3500	A	2002
To: US 60 West of Cumberland C.H.				
(45) (60)	2.42	6200	F	2002
To: 24-600 Cumberland C.H.				
From: 24-600 Cumberland CH				
(45) (60)	1.09	2400	F	2002
To: SR 13 Old Buckingham Rd				
(45) (60)	1.34	2400	N	2002
To: US 60 East of Cumberland C.H.				
From: US 60 East of Cumberland				
(45)	4.85	1400	F	2002
To: 24-616				
(45)	6.60	1100	F	2002
To: 24-690 North of Whiteville				
From: 24-690 North of Whiteville				
(45)	2.20	1600	F	2002
To: 24-649				
(45)	0.75	860	F	2002
To: Goochland County Line				
From: Buckingham County Line				
(60)	4.06	2400	F	2002
To: SR 45 West of Cumberland CH				
(60)	2.42	6200	F	2002
To: 24-600 Cumberland CH				
(60)	1.09	2400	F	2002
To: SR 13 Old Buckingham Rd				
(60)	1.34	2400	N	2002
To: SR 45 East of Cumberland CH				
(60)	6.05	4100	F	2002
To: Powhatan County Line				
From: 24-610				
(734) 14	0.50	80	R	07/11/2000
To: Cumberland County Line				
From: US 60 NORTH				
(600)	0.14	380	R	1999
To: US 60 SOUTH				
(600)	0.04	1300	F	2002
To: 24-710				
(600)	1.33	1000	F	2002
To: 24-642				
(600)	0.86	680	F	2002
To: 24-643				
(600)	1.58	570	F	2002
To: 24-654				
(600)	1.90	330	R	1999
To: 24-620				
(600)	3.64	230	R	1999
To: 24-638				

Route	Length	AADT	QA	Year
Cumberland County				
From: 24-638				
(600)	5.27	220	R	1999
To: 24-653				
(600)	1.58	420	R	1999
To: 24-677				
(600)	1.52	440	F	2002
To: 24-657				
(600)	1.97	600	F	2002
To: 24-702				
(600)	0.80	740	F	2002
To: ECL Farmville				
From: WCL Farmville				
(600)	1.83	1400	F	2002
To: 24-637				
(600)	2.34	1100	R	1999
To: 24-636				
(600)	2.95	1000	R	1999
To: Buckingham County Line; 14-600				
From: 24-626				
(601)	1.50	100	R	03/06/2002
To: SR 45 North				
From: SR 45 South				
(601)	1.40	320	R	1999
To: 24-647				
(601)	1.75	320	R	1999
To: US 60				
From: SR 45				
(602)	5.39	170	R	1999
To: 24-603				
(602)	1.20	240	R	1999
To: 24-605				
(602)	0.80	230	R	1999
To: 24-711				
(602)	0.20	320	R	1999
To: 24-690				
From: 24-602				
(603)	0.80	2	R	03/06/2002
To: Goochland County Line				
From: 24-686				
(604)	0.80	20	R	03/06/2002
To: Dead End				
From: 24-690				
(605)	3.40	60	R	03/06/2002
To: 3.40 MS 24-690				
(605)	1.00	60	R	1999
To: 24-602				
From: Powhatan County Line				
(606)	0.90	150	R	03/11/2002
To: US 60				
From: SR 45				
(607)	1.40	200	R	03/11/2002
To: 24-616				
From: 24-624				
(608)	1.45	80	R	03/04/2002
To: 24-615				

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Cumberland Maintenance Area

Route	Length	AADT	QA	Year
Cumberland County				
From: 24-615				
(608)	1.47	60	R	03/04/2002
To: 24-613				
(608)	1.22	100	R	03/06/2002
To: 24-612				
(608)	0.80	70	R	03/06/2002
To: 24-609				
(608)	0.10	30	R	03/06/2002
To: Dead End				
From: 24-610				
(609)	1.25	90	R	1999
To: 1.25 MS 24-610				
(609)	0.35	60	R	1999
To: 24-608				
From: Buckingham County Line				
(610)	2.90	450	F	2002
To: 24-690				
From: SR 45				
(611)	2.50	310	R	03/06/2002
To: 24-690				
From: 24-608				
(612)	2.50	80	R	03/06/2002
To: 2.50 MN 24-608				
(612)	0.82	180	R	1999
To: 24-714				
(612)	0.18	20	R	03/06/2002
To: 24-690				
From: Buckingham County Line				
(613)	1.50	20	R	03/04/2002
To: 24-672				
(613)	1.55	40	R	03/04/2002
To: 24-608				
From: Dead End .90 MW 45				
(614)	0.90	80	R	1999
To: SR 45				
(614)	1.20	30	R	03/06/2002
To: Dead End				
From: 24-608				
(615)	1.80	40	R	03/04/2002
To: 24-663 WEST				
(615)	0.10	60	R	03/06/2002
To: 24-663 EAST				
(615)	1.77	30	R	03/06/2002
To: 1.78 ME 24-663 EAST				
(615)	0.03	50	R	03/06/2002
To: SR 45				
From: SR 45 SOUTH				
(616)	2.40	220	R	1999
To: 24-654				
(616)	4.08	150	R	1999
To: 24-607				
(616)	2.30	250	R	1999
To: SR 45 NORTH				

Route	Length	AADT	QA	Year
Cumberland County				
From: Buckingham County Line				
(617)	0.25	300	R	03/04/2002
To: 24-622				
From: SR 45				
(618)	0.34	20	R	03/06/2002
To: Dead End				
From: US 60 WEST				
(619)	0.36	70	R	03/06/2002
To: US 60 EAST				
From: Amelia County Line				
(620)	0.80	50	R	03/11/2002
To: 24-600				
From: Amelia County Line				
(621)	2.00	60	R	03/11/2002
To: SR 13				
From: US 60				
(622)	3.33	1700	F	2002
To: 24-627; 24-629				
(622)	1.61	1100	F	2002
To: 24-650				
(622)	0.57	830	F	2002
To: 24-672 EAST				
From: 24-672 WEST				
(622)	1.14	370	R	1999
To: Buckingham County Line				
From: 24-622 North				
(623)	1.95	90	R	03/04/2002
To: 24-624				
(623)	2.60	470	R	1999
To: 24-626				
(623)	0.22	690	R	1999
To: 24-622 South				
From: SR 45				
(624)	2.20	70	R	03/04/2002
To: 24-626 SOUTH				
(624)	0.80	80	R	03/04/2002
To: 24-626 NORTH				
(624)	2.35	40	R	03/04/2002
To: 2.35 MS 24-626				
(624)	0.35	60	R	03/04/2002
To: 24-608				
(624)	0.80	140	R	1999
To: 24-696				
(624)	1.50	240	R	1999
To: 24-623				
From: Dead End				
(625)	1.10	30	R	03/06/2002
To: SR 45				
From: 24-623				
(626)	2.30	110	R	03/04/2002
To: 24-624 SOUTH				
From: 24-624 NORTH				
(626)	1.19	50	R	03/04/2002
To: 24-601				
(626)	1.20	50	R	03/04/2002
To: SR 45				

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Cumberland Maintenance Area

Route	Length	AADT	QA	Year
Cumberland County				
From: 24-622 EAST				
(627)	0.25	60	R	1999
To: 24-730				
From: 24-730				
(627)	1.05	60	R	1999
To: 24-622 WEST				
From: US 60				
(628)	3.86	120	R	03/04/2002
To: 24-629				
From: US 60				
(629)	0.92	210	R	1999
To: 24-633				
From: 24-633				
(629)	3.28	60	R	03/04/2002
To: 24-628				
From: 24-628				
(629)	0.80	150	R	1999
To: 24-666				
From: 24-666				
(629)	0.75	200	F	2002
To: 24-622; 24-627				
From: 24-9111				
(630)	0.10	210	R	1999
To: US 60				
From: SR 45				
(631)	0.50	600	F	2002
To: 24-639				
From: 24-639				
(631)	3.60	260	R	1999
To: 24-644				
From: 24-644				
(631)	0.80	80	R	03/11/2002
To: 24-600				
From: Buckingham County Line				
(632)	2.80	150	R	1999
To: 24-652				
From: 24-652				
(632)	0.40	20	R	03/04/2002
To: US 60				
From: Dead End				
(633)	1.87	110	R	1999
To: SR 45 NORTH				
From: SR 45 SOUTH				
(633)	2.09	260	R	1999
To: US 60				
From: US 60				
(633)	1.04	30	R	03/04/2002
To: 24-629				
From: Buckingham County Line				
(634)	3.45	590	R	03/06/2002
To: SR 45				
From: 24-637				
(635)	2.80	240	R	1999
To: 24-636				
From: 24-636				
(635)	1.40	60	R	03/06/2002
To: Dead End				
From: Buckingham County Line				
(636)	1.20	420	R	1999
To: 24-635				
From: 24-635				
(636)	1.00	350	F	2002
To: 24-600				
From: 24-600				
(636)	1.80	460	F	2002
To: SR 45				

Route	Length	AADT	QA	Year
Cumberland County				
From: SR 45				
(636)	0.30	40	R	03/05/2002
To: Dead End				
From: 24-668				
(637)	1.42	270	R	1999
To: 24-635				
From: 24-635				
(637)	0.15	460	R	1999
To: 24-600				
From: 24-600				
(637)	0.90	190	F	2002
To: SR 45				
From: SR 45				
(638)	2.50	740	F	2002
To: 24-640				
From: 24-640				
(638)	3.20	350	F	2002
To: 24-639				
From: 24-639				
(638)	2.49	170	F	2002
To: 24-600				
From: 24-638				
(639)	4.64	210	F	2002
To: 24-631				
From: 24-638				
(640)	4.20	320	R	1999
To: SR 45				
From: 24-631				
(641)	1.80	120	R	1999
To: 24-642				
From: Dead End				
(642)	0.40	20	R	03/06/2002
To: 24-641				
From: 24-641				
(642)	0.40	150	R	1999
To: 24-600				
From: 24-600				
(643)	2.50	180	R	03/11/2002
To: SR 13				
From: 24-600				
(644)	1.20	30	R	03/11/2002
To: 24-631				
From: SR 13				
(645)	0.80	260	R	1999
To: 24-646				
From: 24-646				
(645)	1.95	210	R	1999
To: 24-654				
From: 24-645				
(646)	1.69	50	R	03/11/2002
To: US 60 WEST				
From: US 60 EAST				
(646)	1.10	50	R	03/11/2002
To: SR 45				
From: 24-601				
(647)	2.50	20	R	03/11/2002
To: 24-654				
From: Dead End				
(648)	0.15	8	R	03/11/2002
To: 24-616				
From: SR 45 NORTH				
(649)	0.10	60	F	2002
To: 24-665				

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Cumberland Maintenance Area

Route	Length	AADT	QA	Year
Cumberland County				
From: 24-665				
(649) To: SR 45 SOUTH	0.25	49	F	2002
From: Buckingham County Line				
(650) To: 24-622	2.13	260	F	2002
From: Dead End				
(651) To: 24-636	0.50	30	R	03/06/2002
From: 24-632				
(652) To: US 60	0.10	200	R	03/04/2002
From: Dead End				
(653) To: 24-600	1.70	60	R	03/05/2002
From: 24-600				
(653) To: 24-638	4.70	170	R	03/05/2002
From: 24-600				
(654) To: 24-674	0.50	170	R	1999
From: 24-674				
(654) To: SR 13 WEST	2.60	230	R	1999
From: SR 13 EAST				
(654) To: US 60	6.00	240	R	1999
From: US 60				
(654) To: 24-685	0.90	220	R	1999
From: 24-685				
(654) To: 24-647	1.20	100	R	1999
From: 24-647				
(654) To: 24-661	0.60	90	R	1999
From: 24-661				
(654) To: 24-616	1.50	100	R	03/11/2002
From: 24-616				
(655) To: Dead End	0.40	30	R	03/11/2002
From: 24-649 WEST				
(656) To: 24-649 EAST	0.15	80	R	1999
From: 24-600				
(657) To: SR 45	3.57	170	R	03/05/2002
From: 24-657				
(658) To: Dead End	0.10	20	R	03/04/2002
From: 24-684				
(659) To: Dead End	0.43	40	R	03/11/2002
From: 24-640				
(660) To: 1.00 ME 24-640	1.00	120	R	1999
From: 2.00				
(660) To: 24-639	2.00	90	R	1999
From: 24-654				
(661) To: 24-616	1.40	30	R	03/11/2002

Route	Length	AADT	QA	Year
Cumberland County				
From: Dead End				
(662) To: 0.20 MN Dead End	0.20	100	R	1999
From: 0.20 MN Dead End				
(662) To: SR 13	1.00	170	R	1999
From: SR 45				
(663) To: 24-615 WEST	1.90	130	R	1999
From: 24-615 EAST				
(663) To: Dead End	1.00	30	R	03/06/2002
From: 24-600				
(664) To: 24-679	1.10	30	R	03/12/2002
From: 24-679				
(664) To: 24-638	2.20	70	R	1999
From: SR 45				
(665) To: 24-649	0.07	120	R	1999
From: 24-649				
(665) To: Dead End	0.06	30	R	1999
From: Dead End				
(666) To: 24-629	0.77	230	R	1999
From: Dead End				
(667) To: 24-654	1.12	70	R	03/11/2002
From: 24-637				
(668) To: 24-716	1.05	190	R	1999
From: 24-716				
(668) To: 0.25 ME 24-716	0.25	40	R	1999
From: 0.25 ME 24-716				
(668) To: 24-635	1.01	50	R	1999
From: SR 45				
(669) To: US 60 EAST	1.90	470	R	1999
From: US 60 WEST				
(669) To: Dead End	0.60	50	R	03/06/2002
From: SR 45				
(670) To: US 60	0.40	280	R	03/11/2002
From: 24-696				
(671) To: 24-672	0.60	40	R	03/04/2002
From: 24-622				
(672) To: 24-694	3.38	240	R	1999
From: 24-694				
(672) To: 24-708	0.80	140	R	1999
From: 24-708				
(672) To: 0.75 MN 24-708	0.75	80	R	1999
From: 0.75 MN 24-708				
(672) To: 24-613	0.40	30	R	03/04/2002

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Cumberland Maintenance Area

Route	Length	AADT	QA	Year
Cumberland County				
From: 24-600				
(673) To: 24-638	2.60	40	R	03/06/2002
From: Dead End				
(674) To: 24-719	0.40	70	R	1999
From: 24-719				
(674) To: 24-654	0.80	140	R	1999
From: Dead End				
(675) To: 24-638	1.70	20	R	03/06/2002
From: SR 45				
(676) To: 24-692	0.75	300	R	1999
From: 24-692				
(676) To: Dead End	2.00	130	R	1999
From: Dead End				
(677) To: 24-600	1.00	20	R	03/05/2002
From: 24-638; 24-679				
(678) To: Dead End	0.50	50	R	03/06/2002
From: 24-664				
(679) To: 24-638; 24-678	2.00	50	R	03/06/2002
From: Dead End				
(680) To: SR 45	0.80	30	R	03/06/2002
From: Dead End				
(681) To: 24-654	1.00	60	R	03/11/2002
From: SR 13				
(682) To: US 60; SR 45	0.50	260	R	03/11/2002
From: Dead End				
(683) To: SR 45	0.40	10	R	03/06/2002
From: SR 45; 24-616				
(684) To: 24-659	1.00	1100	F	2002
From: 24-659				
(684) To: Powhatan County Line	0.03	1100	F	2002
From: 24-654				
(685) To: Dead End	1.00	60	R	03/11/2002
From: 24-610				
(686) To: 24-604	2.80	80	R	03/06/2002
From: 24-604				
(686) To: 24-690	0.90	40	R	03/06/2002
From: Dead End				
(687) To: 24-616	2.20	70	R	03/11/2002
From: 24-639				
(688) To: Dead End	1.10	40	R	03/06/2002

Route	Length	AADT	QA	Year
Cumberland County				
From: Dead End				
(689) To: SR 45; 24-690	0.50	70	R	1999
From: SR 45; 24-689				
(690) To: 24-714	2.94	600	F	2002
From: 24-714				
(690) To: 24-686	3.89	620	F	2002
From: 24-686				
(690) To: Buckingham County Line	4.53	580	F	2002
From: Dead End				
(691) To: SR 45	0.50	40	R	03/06/2002
From: Dead End				
(692) To: 24-676	0.65	20	R	03/06/2002
From: Dead End				
(693) To: 24-639	1.30	50	R	03/06/2002
From: 24-672				
(694) To: Buckingham County Line	0.60	170	R	03/04/2002
From: Dead End				
(695) To: 24-699	0.25	20	R	03/06/2002
From: Buckingham County Line				
(696) To: 24-672	0.70	60	R	1999
From: 24-672				
(696) To: 24-671	0.70	40	R	03/04/2002
From: 24-671				
(696) To: 24-624	1.00	120	R	1999
From: SR 45				
(697) To: Dead End	1.20	30	R	03/06/2002
From: Dead End				
(698) To: 24-657	0.25	50	R	03/04/2002
From: Dead End				
(699) To: 24-695	0.60	140	R	1999
From: 24-695				
(699) To: SR 45	0.20	170	R	1999
From: Dead End				
(700) To: 24-690	0.70	40	R	03/06/2002
From: Dead End				
(701) To: SR 45	1.00	20	R	03/06/2002
From: 24-600				
(702) To: Dead End	0.50	20	R	03/05/2002
From: Dead End				
(703) To: 24-631	1.05	60	R	03/06/2002

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Cumberland Maintenance Area

Route	Length	AADT	QA	Year
Cumberland County				
From: 24-600				
(704) To: Dead End	0.25	30	R	03/06/2002
From: SR 45				
(705) To: Dead End	0.30	20	R	03/06/2002
From: SR 45				
(706) To: Dead End	0.40	2	R	03/06/2002
From: 24-657				
(707) To: Dead End	0.40	100	R	03/04/2002
From: Dead End				
(708) To: 24-672	0.40	50	R	03/04/2002
From: Dead End				
(709) To: SR 45	0.40	40	R	03/05/2002
From: US 60				
(710) To: 24-600	0.17	200	R	03/11/2002
From: 24-602				
(711) To: Dead End	0.95	30	R	03/06/2002
From: SR 45				
(712) To: 24-657	1.60	370	R	03/04/2002
From: Dead End				
(713) To: 24-690	0.93	70	R	1999
From: 24-612				
(714) To: 24-690	0.20	210	R	1999
From: Dead End				
(715) To: 24-690	0.45	50	R	03/06/2002
From: Dead End				
(716) To: 24-668	0.34	170	R	1999
From: Dead End				
(717) To: 24-600	0.63	60	R	03/11/2002
From: 24-640				
(718) To: Dead End	0.30	30	R	03/11/2002
From: 24-674				
(719) To: Dead End	0.32	40	R	03/11/2002
From: Dead End				
(720) To: 24-653	0.25	40	R	03/05/2002
From: SR 45				
(721) To: Dead End	0.18	20	R	03/06/2002
From: 24-650				
(722) To: Dead End	0.05	40	R	03/04/2002

Route	Length	AADT	QA	Year
Cumberland County				
From: Dead End				
(723) To: SR 13	0.40	70	R	03/11/2002
From: Dead End				
(724) To: US 60	0.50	50	R	03/04/2002
From: Dead End				
(725) To: 24-638	0.35	50	R	03/12/2002
From: 24-600				
(726) To: Dead End	0.31	60	R	03/11/2002
From: SR 45				
(727) To: Dead End	0.08	110	R	1999
From: US 60				
(728) To: Dead End	0.65	50	R	1999
From: Dead End/				
(729) To: 24-00602(B)/	0.33	NA		
From: Dead End				
(730) To: 24-627	0.25	40	R	03/04/2002
From: Cul-de-Sac				
(731) To: 24-600	0.39	40	R	03/11/2002
From: Dead End				
(733) To: 24-657	0.20	50	R	03/04/2002
From: 24-626				
(735) To: Cul-de-Sac	1.00	20	R	03/06/2002
From: Cul-de-Sac/				
(737) To: 24-00600(B)/24-00643(U)/	0.33	NA		
From: SR 45				
(1008) To: Dead End	0.46	100	R	1999
From: 24-1013				
(1009) To: 24-1010	0.10	130	R	1999
From: 24-1010				
(1009) To: SR 45	0.10	80	R	03/04/2002
From: 24-1009				
(1010) To: 24-1011	0.17	80	R	1999
From: 24-1011				
(1010) To: 24-1012	0.13	40	R	1999
From: 24-1013				
(1011) To: 24-1010	0.09	90	R	1999
From: 24-1010				
(1011) To: SR 45	0.08	230	R	1999
From: Dead End				
(1012) To: 24-1014	0.12	30	R	1999

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Cumberland Maintenance Area

Route	Length	AADT	QA	Year
Cumberland County				
From: 24-1014				
1012	0.08	80	R	1999
To: 24-1013				
From: 24-1013				
1012	0.09	40	R	03/04/2002
To: 24-1010				
From: 24-1010				
1012	0.11	60	R	03/04/2002
To: SR 45				
From: 24-1009				
1013	0.22	90	R	1999
To: 24-1011				
From: 24-1011				
1013	0.12	60	R	1999
To: 24-1012				
From: 24-1012				
1014	0.07	70	R	1999
To: 24-1015				
From: Cul-de-Sac				
1015	0.11	20	R	1999
To: 24-1014				
From: 24-1014				
1015	0.17	20	R	1999
To: Cul-de-Sac .17ME				
From: Cul-de-Sac				
1020	0.30	90	R	03/06/2002
To: SR 45				
From: 24-630				
9111	0.13	1400	R	1999
To: US 60				
From: US 60				
9780	0.09	60	R	1999
To: 24-628				