

**2002**

**Virginia Department of Transportation  
Daily Traffic Volume Estimates**

**Special Locality Report**

**139**

Town of Wytheville

Prepared By

**Virginia Department of Transportation  
Mobility Management Division**

In Cooperation With

**U.S. Department of Transportation  
Federal Highway Administration**

Virginia Department of Transportation  
Mobility Management Division  
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management’s Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

## **Publication Notes**

### **Parallel Roads**

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

---

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT’s Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

**Route:** The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

**Length:** Length of the traffic segment in miles.

**AADT:** Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

**QA:** Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

**4Tire:** Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

**Bus:** Percentage of the traffic volume made up of busses.

**2Axle Truck:** Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck:** Percentage of the traffic volume made up of single unit trucks with three or more axles.

**1Trail Truck:** Percentage of the traffic volume made up of units with a single trailer.

**2Trail Truck:** Percentage of the traffic volume made up of units with more than one trailer.

**QC:** Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

**Peak Hour:** The estimate of the traffic volume for the 30<sup>th</sup> highest traffic volume occurring in a one-year period divided by the AADT for the same one-year period.

**QK:** Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During 12 Months of Continuous Traffic Data
- B Factor based on 30th Highest Hour Observed During Less than 12 Months of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of 30th Highest Hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

**Dir Factor:** The estimate of the portion of the traffic volume traveling in the peak direction during the Peak Hour..

**AAWDT:** Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

**QW:** Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

**Year:** Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

# Route Shield Legend

## Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Secondary Route

## Special Routes



Bus - Business Route

Bypas - Bypass Route

Truck - Truck Route



ALT - Alternate Route

Wve - Wve Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation  
 Mobility Management Division  
 2002  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 Town of Wytheville

Route	Length	AADT	QA	Year
<b>Town of Wytheville</b>				
From WCL Wytheville				
W Lee Hwy	0.29	4600	G	2002
To 24th St				
12th St	2.03	8000	G	2002
To US 21 Main St				
From 12th St				
Main St	0.31	8400	G	2002
To 4th St				
Main St	0.33	9800	G	2002
To 5th St				
Main St	0.20	9300	G	2002
To 11th St				
E Main St	0.50	15000	G	2002
To Liberty St				
	0.78	10000	G	2002
To 139-3 Lithia Rd				
	0.08	10000	N	2002
To I-81				
	0.96		See I-81	
Combined Traffic:		50000	G	
To NCL Wytheville				
From SCL Wytheville				
Grayson Street	0.93	4800	G	2002
To Main Street				
From Grayson St				
Main Street	0.49	6500	G	2002
To US 11 12Th St				
Main St	0.31	8400	G	2002
To MAIN ST				
From Main Street				
4th St	0.06	7300	G	2002
To Monroe Street				
4th St	0.47	11000	G	2002
To Ridge Rd				
From W Ridge Rd				
4th St	0.40	11000	G	2002
To Tazewell St				
4th St	0.12	11000	G	2002
To I-81; US 52				
From NCL Wytheville				
	0.93		See I-81	
Combined Traffic:		50000	G	
To US 11				
	1.29		See I-81	
Combined Traffic:		45000	G	
To I-77 Wytheville				
	1.99		See I-81	
Combined Traffic:		26000	G	
To HOLSTON I-81 SB RAMP				
From I-81 SB Ramp				
	1.89	2400	G	2002
To WCL Wytheville				
North South				
	0.93	25000	A	2002
Combined Traffic:		50000	G	
To US 11				

Route	Length	AADT	QA	Year
<b>Town of Wytheville</b>				
North South				
	1.29	22000	G	2002
Combined Traffic:		45000	G	
To I-81 Wytheville				
North				
	0.59	14000	G	2002
Combined Traffic:		28000	G	
To Peppers Ferry Rd				
North				
	0.23	14000	G	2002
Combined Traffic:		28000	G	
To NCL Wytheville				
South North				
	0.96	25000	G	2002
Combined Traffic:		50000	G	
To US 11				
South North				
	0.82	22000	G	2002
Combined Traffic:		45000	G	
To I-81 Wytheville				
South				
	1.15	14000	G	2002
Combined Traffic:		28000	G	
To NCL Wytheville				
North				
	2.03	13000	G	2002
Combined Traffic:		25000	G	
To US 21; US 52				
North				
	2.27	13000	G	2002
Combined Traffic:		26000	G	
To I-77 Wytheville				
North				
	0.82	22000	G	2002
Combined Traffic:		45000	G	
To US 11				
North				
	0.96	25000	G	2002
Combined Traffic:		50000	G	
To NCL Wytheville				
South				
	2.71	12000	G	2002
Combined Traffic:		25000	G	
To US 21; US 52				
South				
	1.99	13000	G	2002
Combined Traffic:		26000	G	
To I-77 Wytheville				
South				
	1.29	22000	G	2002
Combined Traffic:		45000	G	
To US 11				
South				
	0.93	25000	A	2002
Combined Traffic:		50000	G	
To NCL Wytheville				
From US 52				
Fairview Rd	1.19	1700	G	2002
To NCL Wytheville				

Virginia Department of Transportation  
 Mobility Management Division  
 2002  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 Town of Wytheville

Route	Length	AADT	QA	Year
<b>Town of Wytheville</b>				
From: US 52 4Th St ② Holston Rd To: Cove Rd	1.24	1500	G	2002
From: US 11 Main St ③ Lithia Rd To: Nye Rd	0.48	1400	G	2002
From: .25 Mi. S Peppers Ferry Rd ④ Nye Rd To: Peppers Ferry Rd	1.25	1000	G	2002
From: WCL Wytheville ⑤250 Old Stage Rd To: US 21 Grayson St	1.63	1400	G	2002
From: Petunia Rd ⑤252 W Ridge Rd To: Old WCL Wytheville	0.14	640	G	2002
From: Old WCL Wytheville ⑤252 W Ridge St To: 18Th St	1.55	1300	G	2002
From: 18Th St ⑤252 W Ridge Rd To: US 21 4Th St	0.49	1600	G	2002
From: US 11 Main St ⑤253 Withers Rd To: 11th St	0.25	3700	G	2002
From: Withers St ⑤253 11th St To: US 11 Main St	0.31	2700	G	2002
From: US 11 Main St ⑤253 11th St To: Monroe St	0.06	7800	G	2002
From: Monroe St ⑤253 11Th-North St To: Fisher Rd	0.13	2100	G	2002
From: Fisher Rd ⑤253 Fisher Rd To: Pine St	0.14	1300	G	2002
From: Peppers Ferry Rd ⑤255 Cove Rd To: Holston Rd	0.52	2600	G	2002
From: Holston Rd ⑤255 Cove Rd To: .30 Mi. N Holston Rd	0.32	1200	G	2002
From: .30 Mi. N Holston Rd ⑤255 Cove Rd To: NCL Wytheville	0.29	1000	G	2002
From: 12Th St ⑤256 Spring St To: 4Th St	0.30	1800	G	2002
From: 4Th St ⑤256 Spring St To: 11Th St	0.54	2300	G	2002
From: Main St ⑤257 Tazewell St To: Monroe St	0.06	1500	G	2002
From: 12Th St US 11 ⑤258 Monroe St To: 4Th St US 21	0.31	3500	G	2002
From: US 21 4Th St ⑤258 Monroe St To: 1St Street	0.19	6600	G	2002
From: N 1St Street ⑤258 Monroe St To: N 5Th St	0.15	6100	G	2002

Route	Length	AADT	QA	Year
<b>Town of Wytheville</b>				
From: 5Th St ⑤258 Monroe St To: 11Th St	0.19	5900	G	2002
From: 11Th St ⑤258 Peppers Ferry Rd To: Cove Rd	0.46	7200	G	2002
From: Cove Rd ⑤258 Peppers Ferry Rd To: Ramp to I-77	0.67	6200	G	2002
From: Ramp to I-77 ⑤258 Peppers Ferry Rd To: ECL Wytheville	0.19	1500	G	2002
From: ECL Wytheville ⑤258 Peppers Ferry Rd To: JB-139 ECL Wytheville	0.47	NA		
From: JB-139 ECL Wytheville ⑤258 Peppers Ferry Rd To: 98-610 JB-139 ECL Wytheville				
From: Main St US 11 ⑤260 12th St To: Union St	0.29	2800	G	2002
From: Union St ⑤260 Union St To: 12Th St	0.30	2800	G	2002
From: 4Th St ⑤260 Withers St To: 11Th St	0.56	3600	G	2002
From: Marshall St ⑤261 4th St To: Withers St	0.31	2400	G	2002
From: Withers St ⑤261 4th St To: US 11 Main St	0.30	2900	G	2002
From: US 11 Main St ⑤262 Marshall St To: 4Th St	0.91	1900	G	2002
From: 4Th St ⑤262 Marshall St To: Main St US 11				
From: Main St US 11 ⑤264 Pine St To: US 11 Lee Hwy	0.38	1900	G	2002
From: US 11 Lee Hwy ⑤264 Pine St To: US 21 4Th St	0.44	360	G	2002
From: US 21 4Th St ⑤264 Pine St To: Fisher Rd				
From: Fisher Rd 16th St To: Spring St	150		G	2002
From: Spring St 16th St To: Franklin St				
From: Washington St Church St To: Withers St	1000		G	2002
From: Withers St Mountain View Dr To: 11Th St	710		G	2002
From: 11Th St Mountain View Dr To: 13Th St				
From: 5Th St Spiller St To: 3Rd St	150		G	2002