2005

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 198

Town of Coeburn

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	te
(F241)	Frontage Road (F	precedes frontage route number)
600	Secondary Route	

Special Routes

Bus	Bus - Business Route		
[29]	Bypas - Bypass Route		
	Truck - Truck Route		
ALT	ALT - Alternate Route		
(220)	Wye - Wye Route connector		
~~~			

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

# Virginia Department of Transportation Traffic Engineering Division 2005 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Coeburn

Posts	Lordon Portion	Learnite AAD	T 04	4	D		Tru		00	K	01/	Dir	A A \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	- OW	
Route	Jurisdiction	Length AAD	I QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	QW
ALT	From:	WCL Coo													
58	Town of Coeburn (Maint: 97)	0.94 <b>1200</b>	0 N	94%	0%	1%	1%	3%	0%	N	0.079	Ν	0.571	13000	N
	To: From:	SR 15	8												
ALT (58)	Town of Coeburn (Maint: 97)	0.13 <b>1200</b>	0 G	94%	0%	1%	1%	3%	0%	F	0.07	F	0.692	13000	G
	Too	W SR 1	58			—									
ALT (58)	From:			0.40/	00/	10/	1%	3%	00/	_	0.074	_	0.550	9300	0
58	Town of Coeburn (Maint: 97)	0.77 <b>870</b> SR 72 South In		94%	0%	1%	1%	3%	0%	г	0.074	Г	0.559	9300	G
ALT	From:	SR 72 East In													
ALT (58)	Town of Coeburn (Maint: 97)	2.71 <b>760</b> 0	) G	94%	0%	1%	1%	3%	0%	F	0.073	F	0.523	8000	G
$\bigcirc$	To	SR 15	8												
	From:	SCL Coe	burn												
(72)	Town of Coeburn (Maint: 97)	0.35 <b>240</b> 0	) N	97%	0%	1%	1%	1%	0%	Ν	0.083	Ν	0.587	2500	Ν
<u> </u>	To: From:	Alt US	58												
72	Town of Coeburn (Maint: 97)	0.19 <b>490</b>	) G	71%	1%	1%	1%	26%	0%	F	0.086	F	0.669	5000	G
<u> </u>	To: From:	SR 15	8			-									
72 (158)	Town of Coeburn (Maint: 97)	0.65 <b>620</b>	) G	99%	0%	1%	0%	0%	0%	F	0.081	F	0.565	6400	G
	To	SR 158 SR 15	8 BUS P												
72	Town of Coeburn (Maint: 97)	1.36 <b>520</b> 0	) G	71%	1%	1%	1%	26%	0%	F	0.078	F	0.527	5400	G
$\overline{}$	То:	NCL Coe	burn												
	From:	ALT US													
(158)	Town of Coeburn (Maint: 97)	0.22 <b>570</b>		99%	0%	1%	0%	0%	0%	F	0.088	F	0.675	5900	G
	To:	97-813 Old Norto SR 72 W		Rd											
(158) (72)	Town of Coeburn (Maint: 97)	0.65 <b>620</b>		99%	0%	1%	0%	0%	0%	F	0.081	F	0.565	6400	G
158 72	romrer coopern (mainte er)			0070	070		070	070	070	•	0.001	•	0.000	0.00	Ū
(150)	Town of Coeburn (Maint: 97)	SR 72 E 1.04 <b>980</b>		99%	0%	1%	0%	0%	0%	С	0.088	F	0.516	1000	G
(158)	To:	ECL Coe		3376	0 /0	170	0 /0	070	0 /0	J	0.000	•	0.010	1000	J
	From:	ALT US				1									
158	Town of Coeburn (Maint: 97)	0.33 490		94%	1%	1%	0%	4%	0%	С	0.085	F	0.713	5100	G
, ko	To:	SR 72								-				<del>-</del>	-

## Virginia Department of Transportation Traffic Engineering Division 2005 Annual Average Daily Traffic Volume Estimates By Section of Route

	-							
		To	own	0	f C	oeb	urn	

					_		Tru	ıck			K		Dir			
Route	Length	AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK	Factor	AAWDT	QW	Year
Town of Coeburn		From	•			CL	Coeburn				1					
158 813	0.12	650	N	89%	0%	1%	1%	9%	0%	N	0.099	Ν	0.551	670	Ν	2005
	2.42	From		200/	201		RT 690	00/	201	_		_	0.045			
158 (813)	0.19	3700 To	G	89%	0%	1% SR	1% 72 W INT	9%	0%	С	0.089	F	0.815	3900	G	2005
		From					L Coeburn									
646 Coeburn Mt.Rd	0.72	1900	G	98%	0%	1%	0%	1%	0%	F	0.088	F	0.57	2000	G	2005
		To	1				SR 72									
(658) River View Rd	0.19	2800	G	98%	0%	0%	L Coeburn 0%	0%	0%	С	0.083	F	0.564	2900	G	2005
River View Rd	0.10	To	_	0070	070		7-1129	070	070		— <u> </u>		0.001	2000		2000
River View Rd	0.55	1300 From	G	98%	0%	0%	0%	0%	0%	F	0.088	F	0.532	1300	G	2005
		To From					SR 72									
658	0.12	<b>2000</b>	R			~~~	~ .				NA			NA		07/29/2003
		From			0.7		Coeburn	. 5.								
690	0.03	400	R		97	-813 Old f	Norton Coe	burn Rd			NA			NA		1997
970		To From	-			A	lt US 58									
690	0.49	320	R								NA			NA		1997
97		То					97-646									
	0.20	120	R			97-6	90 WEST				NA			NA		1997
696	0.20	To				97-0	590 EAST							INA		1997
		From				97-658 I	River View	⁷ Rd								
718	160	R								NA			NA		07/29/2003	
		To From	1				ead End									
719	0.20	150	R			D	ead End				NA			NA		1997
(1,9)		To	:				SR 72									
		From					97-690									
(754)	0.09	130 To	R				97-696				NA			NA		1997
		From					7-1129									
756	0.10	200	R				7 112)				NA			NA		1997
97)		То				D	ead End									
$\bigcirc$	0.40	From		000/	00/		L Coeburn		00/	N.I.	0.000	N.	0.554	070	N.	2005
813	0.12	650	N	89%	0%	1%	1%	9%	0%	N	0.099	N	0.551	670	N	2005
<u>(813)</u>	0.19	3700	G	89%	0%	1%	Prospect A	9%	0%	С	0.089	F	0.815	3900	G	2005
(8 ₁ 3)		То					ALT; SR									
		From					SR 72									
877	0.07	<b>NA</b>				D	and End				NA			NA		
		From		Dead End 97-658; 97-877 Gap Terminus												
878	0.04	NA			,	7-030, 97-0	377 Gap 10	Jillillus			NA			NA		
97		То	Dead End													
$\bigcirc$	0.00	From				Priv	ate Drive							NIA		
881)	0.08	NA To									NA			NA		
		From					SR 72									
884	0.43	NA	-								NA			NA		
		To					SR 158									
(1101)	0.45	790	R				SR 72				 NA			NA		10/25/2000
97		7 9 0 To				97-1	105 WEST	,								.5,25,2000

# Virginia Department of Transportation Traffic Engineering Division 2005 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Coeburn

						Town of Coeb								
Route	Length	AADT	QA	4Tire	Bus	Tr 2Axle 3+Axle		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Coeburn		From	1			97-1105 WES	Г		1					
1101	0.04	4800	R			77 1103 WEB	•		NA			NA		10/25/2000
97)		To From				97-1103; 97-110	05							
1101	0.05	850	R						NA			NA		10/25/2000
<u> </u>		To	1			Alt US 58								
	0.15	740	R			Alt US 58			NA			NA		10/28/2000
1102	0.13	740 To	_			SR 72						INA		10/20/2000
		From	4			97-1101 SOUT	Ή		Ì					
1103	0.10	900	R						NA			NA		10/25/2000
		To From				97-1104			_					
1103	0.10	870	R						NA			NA		10/25/2000
		To From				97-1106			$\supset$					
1103	0.51	790	R						NA			NA		10/25/2000
		To	1			97-1101 NORT	Ή		4					
	0.19	120	R			97-1101			NA			NA		10/25/2000
1104	0.13	1 <b>20</b>				07.1100						14/3		10/23/2000
(1104)	0.09	30 From	ī R			97-1109			NA			NA		10/25/2000
1104	0.00	To				97-1106								. 0/20/2000
(1104)	0.12	80 From	R			97-1100			NA			NA		10/25/2000
		Te				Dead End								
		From				Alt US 58								
1105	0.07	4400	R						NA			NA		10/25/2000
		To From				97-1101 WES 97-1101 EAST								
1105)	0.15	2100	R			71-1101 E/IS1			NA			NA		10/25/2000
1105		To				97-1106								
1105	0.30	690 From	R						NA			NA		10/25/2000
97)		To				Dead End								
		From				97-1103								
1106	0.38	460	R						NA 			NA		10/25/2000
	0.40	From				97-1107						NIA		40/05/0000
1106	0.10	1300 To	R			Alt US 58			NA			NA		10/25/2000
		From				97-1106			i i					
(1107)	0.35	470	R						NA			NA		10/25/2000
97		To	:			NCL Coeburn	ı							
$\bigcirc$		From				Alt US 58								
1108	0.07	550	R			97-1105			NA			NA		10/23/2000
		From												
(1100)	0.07	720	R			Alt US 58			NA			NA		10/25/2000
(1109)	0.0.	T-0				97-1105								. 0/20/2000
(1109)	0.07	<b>70</b> From	R			97-1103			NA			NA		10/25/2000
1109		To				97-1104								
1109	0.09	8 From	R			)/-11U <del>1</del>			NA			NA		10/25/2000
97		To				Dead End								
$\widehat{}$		From				Alt US 58								
1110	0.07	180	R			05.1105			NA			NA		10/23/2000
		To				97-1105								
(1111)	0.11	60	R			SR 72			NA			NA		10/23/2000
	0.11	To				Dead End						INA		10/20/2000
			-											

# Virginia Department of Transportation Traffic Engineering Division 2005 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Coeburn

						TOWN OF								
Route	Length	AADT	QA	4Tire	Bus		Truck -Axle 1Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Coeburn		From				07.6	00		1					
1116	0.13	390	R			97-6	90		NA			NA		1993
		To: From:				97-1	128							
(1116) 97	0.10	620	R			an.			NA			NA		10/23/2000
		From:				SR '								
1128	0.10	550	R		97	/-813 Old Nort	on Coeburn Rd		NA			NA		10/23/2000
		To:				97-1	116							
1128	0.15	160	R						NA			NA		10/23/2000
		To:				SR '	72							
	0.23	480	R			SCL Co	eburn		NA			NA		10/23/2000
1129	0.25	400				.= .=						INA		10/23/2000
	0.32	3300 From:	R			97-658 Rive	r View Rd		NA			NA		10/23/2000
1129	0.52	To:			97	7-813 Old Nort	on Coeburn Rd					11/3		10/23/2000
		From	1			Dead			i					
1131	0.07	770	R			Duu	2.10		NA			NA		10/23/2000
97		To				SR '	72							
		From				Dead	End							
1132	0.27	130 To:	R			07.6	00		NA			NA		10/23/2000
		From:				97-6								
	0.07	80	R			Alt U	S 58		NA			NA		10/23/2000
1133	0.07	To:	<u> </u>			Dead	End					11/3		10/23/2000
		From	l			SR '			ĺ					
1135	0.11	190	R			~~~	-		NA		NA		10/23/2000	
97		To				NCL Co	eburn							
		From				Dead	End							
1136	0.10	80	R						NA			NA		10/23/2000
<u> </u>		To:				97-6	90							
	0.07	From	ᄂ			Dead	End					NΙΔ		1002
1137	0.07	30	R						NA —			NA		1993
	0.07	From	ᄂᢩ			0.07 MN I	Dead End					NIA		4000
1137	0.07	<b>70</b>	R			Alt U	S 58		NA			NA		1993
		From	1			97-1								
9556)	0.13	1000	R			<i>71</i> -1.	103		NA			NA		1993
(9556) 97		To				Coeburn M	iddle Sch							
		From:				97-1	101							
9636	0.25	470	R						NA			NA		1993
		To				Coeburn Hi	gh School							
		From	Ļ			Coeburn Eler	nentary Sch		$\Box$					
9637	0.50	1700	R			07.1	102		NA			NA		1993
		10.				97-1	103							