

2004

**Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates**

where available

Special Locality Report

328

Town of Windsor

Prepared By

**Virginia Department of Transportation
Mobility Management Division**

In Cooperation With

**U.S. Department of Transportation
Federal Highway Administration**

Virginia Department of Transportation
Mobility Management Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management's Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT’s Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Secondary Route

Special Routes



Bus - Business Route

Bypas - Bypass Route

Truck - Truck Route



ALT - Alternate Route

Wve - Wye Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
 Mobility Management Division
 2004
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Windsor

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	
							2Axle	3+Axle	1Trail	2Trail							
258 Prince Blvd S	Town of Windsor (Maint: 46)	From: WCL Windsor	0.19	4800	G	87%	1%	2%	1%	9%	0%	F	0.078	F	0.555	4800	G
		To: US 460 Windsor Blvd															
258 Prince Blvd N	Town of Windsor (Maint: 46)	From: NCL Windsor	0.25	5500	G	92%	1%	2%	1%	5%	0%	F	0.076	F	0.599	5500	G
		To: WCL Windsor															
460	Town of Windsor (Maint: 46)	From: US 258	0.07	10000	G	81%	1%	1%	1%	16%	0%	F	0.072	F	0.509	9700	G
		To: 46-610															
460	Town of Windsor (Maint: 46)	From: ECL Windsor	0.45	14000	G	81%	1%	1%	1%	16%	0%	F	0.080	F	0.566	13000	G
		To: WCL Windsor															
460	Town of Windsor (Maint: 46)	From: WCL Windsor	0.74	15000	N	81%	1%	1%	1%	16%	0%	N	0.08	N	0.582	14000	N
		To: ECL Windsor															

Virginia Department of Transportation
 Mobility Management Division
 2004
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Windsor

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail								
Town of Windsor																	
(603) 46	0.41	2300	G	94%	1%	3%	0%	2%	0%	C	0.106	F	0.779	2300	G	2004	
				From:	WCL Windsor												
(603) 46	0.50	2600	G	95%	1%	3%	0%	0%	0%	F	0.139	F	0.619	2600	G	2004	
				From:	US 460 Windsor Blvd												
				To:	46-1805 Roberts Ave												
(603) 46	Church St	0.14	1700	G	95%	1%	3%	0%	0%	F	0.102	F	0.541	1700	G	2004	
				From:	46-1805												
				To:	ECL Windsor												
(610) 46	Court Street	0.24	1000	G	94%	1%	5%	0%	1%	F	0.09	F	0.514	1000	G	2004	
				From:	SCL Windsor												
(610) 46	Court Street	0.07	1200	G	94%	1%	5%	0%	1%	F	0.087	F	0.571	1200	G	2004	
				From:	46-1802 West; N & W St												
(610) 46	Court Street North	0.55	1800	F	97%	2%	0%	0%	0%	C	0.125	F	0.622	1800	F	2004	
				From:	US 460 Windsor Blvd												
				To:	NCL Windsor												
(636) 46	Griffin Street West	0.05	610	R							NA		NA			1999	
				From:	46-603 Bank Street												
(636) 46	Griffin Street East	0.50	400	R							NA		NA			1999	
				From:	46-610 Court St South												
				To:	SCL Windsor												
(1800) 46		0.06	50	R							NA		NA			1999	
				From:	Dead End												
				To:	46-1803												
(1801) 46		0.10	60	R							NA		NA			1999	
				From:	46-603												
				To:	Dead End; Gap Terminus												
(1801) 46		0.01	70	R							NA		NA			1999	
				From:	Dead End; Gap Terminus												
(1801) 46		0.04	190	R							NA		NA			1999	
				From:	46-1802												
				To:	US 460												
(1802) 46		0.13	40	R							NA		NA			1999	
				From:	Dead End												
(1802) 46		0.02	430	R							NA		NA			1999	
				From:	46-1804												
(1802) 46		0.04	180	R							NA		NA			1999	
				From:	46-610												
(1802) 46		0.16	150	R							NA		NA			1999	
				From:	46-603												
				To:	46-1801												
(1803) 46		0.02	120	R							NA		NA			1999	
				From:	Dead End												
(1803) 46		0.08	180	R							NA		NA			1999	
				From:	46-1800												
				To:	US 460												
(1804) 46		0.06	260	R							NA		NA			1999	
				From:	46-1802												
				To:	US 460												
(1805) 46		0.16	750	R							NA		NA			1999	
				From:	US 460												
(1805) 46		0.02	600	R							NA		NA			1999	
				From:	46-1817												
(1805) 46		0.05	720	R							NA		NA			1999	
				From:	46-1814												
				To:	46-603												

Virginia Department of Transportation
 Mobility Management Division
 2004
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Windsor

Route	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
Town of Windsor																
1809 46	0.09	100	R			From: US 460						NA		NA		1999
						To: Dead End										
1810 46	0.02	730	N			From: WCL Windsor						NA		NA		1999
						To: 46-603										
1811 46	0.07	150	R			From: 46-610						NA		NA		1999
						To: 46-1812										
1812 46	0.24	350	R			From: 46-603						NA		NA		1999
						To: 46-1824										
1812 46	0.05	240	R			From: 46-1811						NA		NA		1999
						To: 46-1811										
1812 46	0.02	220	R			From: 46-1813						NA		NA		1999
						To: 46-1813										
1812 46	0.03	20	R			From: Dead End						NA		NA		1999
						To: Dead End										
1813 46	0.29	110	R			From: 46-1812						NA		NA		1999
						To: Dead End										
1814 46	0.29	110	R			From: US 460						NA		NA		1999
						To: 46-1805										
1815 46	0.09	70	R			From: US 258 South						NA		NA		1999
						To: 46-1816										
1815 46	0.08	100	R			From: US 258 North						NA		NA		1999
						To: US 258 North										
1816 46	0.03	70	R			From: 46-1815						NA		NA		1999
						To: Dead End										
1817 46	0.06	240	R			From: 46-1805						NA		NA		1999
						To: 46-1818										
1817 46	0.07	80	R			From: Cul-de-Sac						NA		NA		1999
						To: Cul-de-Sac										
1818 46	0.14	100	R			From: Cul-de-Sac						NA		NA		1999
						To: 46-1817										
1820 46	0.06	560	R			From: US 258						NA		NA		1999
						To: 46-1822										
1820 46	0.18	490	R			From: 46-1823						NA		NA		1999
						To: 46-1823										
1820 46	0.05	90	R			From: 46-1821						NA		NA		1999
						To: 46-1821										
1820 46	0.05	90	R			From: 46-1822						NA		NA		1999
						To: 46-1822										
1821 46	0.06	160	R			From: US 258						NA		NA		1999
						To: 46-1822										
1821 46	0.12	170	R			From: 46-1820						NA		NA		1999
						To: 46-1820										

Virginia Department of Transportation
 Mobility Management Division
 2004
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Windsor

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
Town of Windsor																
1822 46	0.05	50	R			From: 46-1820						NA		NA		1999
1822 46	0.05	49	R			From: 46-1823						NA		NA		1999
1822 46	0.15	110	R			From: 46-1821						NA		NA		1999
1822 46						To: 46-1820										
1823 46	0.14	230	R			From: 46-1822						NA		NA		1999
1823 46						To: 46-1820										
1824 46	0.22	70	R			From: 46-1812						NA		NA		1999
1824 46						To: Cul-de-Sac										
1825 46	0.12	210	R			From: US 460						NA		NA		1999
1825 46						To: 46-1814										
1827 46	0.08	NA				From: 46-600 Lovers Lane						NA		NA		
1827 46						To: 46-1828										
1828 46	0.02	NA				From: Dead End						NA		NA		
1828 46						To: Dead End										
9208 46	0.10	390	R			From: Windsor High School						NA		NA		1999
9208 46						To: 46-603										