

2002

**Virginia Department of Transportation
Daily Traffic Volume Estimates**

Special Locality Report

340

Town of Castlewood

Prepared By

**Virginia Department of Transportation
Mobility Management Division**

In Cooperation With

**U.S. Department of Transportation
Federal Highway Administration**

Virginia Department of Transportation
Mobility Management Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management’s Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT’s Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

Peak Hour: The estimate of the traffic volume for the 30th highest traffic volume occurring in a one-year period divided by the AADT for the same one-year period.

QK: Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During 12 Months of Continuous Traffic Data
- B Factor based on 30th Highest Hour Observed During Less than 12 Months of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of 30th Highest Hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the Peak Hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Secondary Route

Special Routes



Bus - Business Route

Bypas - Bypass Route

Truck - Truck Route



ALT - Alternate Route

Wve - Wve Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Castlewood

| Route | Length | AADT | QA | Year | |
|---------------------------|------------------------------|------|-------|------|------------|
| Town of Castlewood | | | | | |
| ALT 58 | From: Wise County Line | 2.56 | 13000 | A | 2002 |
| | To: SR 65 | | | | |
| ALT 58 | From: SR 65 | 1.04 | 10000 | F | 2002 |
| | To: WCL Castlewood | | | | |
| 63 | From: Russell County Line | 1.50 | 5800 | F | 2002 |
| | To: NCL Castlewood | | | | |
| 65 | From: WCL Castlewood | 3.02 | 1200 | N | 2002 |
| | To: US 58 ALT Banners Corner | | | | |
| 611 83 | From: SCL Castlewood | 0.63 | 490 | N | 1999 |
| | To: WCL Castlewood | | | | |
| 611 83 | From: SR 65 EAST | 0.28 | 480 | R | 1999 |
| | To: WCL Castlewood | | | | |
| 615 83 | From: 83-683 | 0.40 | 310 | F | 2002 |
| | To: 83-695 | | | | |
| 615 83 | From: 83-695 | 1.66 | 590 | F | 2002 |
| | To: 83-628 WEST | | | | |
| 615 83 | From: 83-628 WEST | 0.12 | 110 | N | 2002 |
| | To: ECL Castlewood | | | | |
| 628 83 | From: Wise County Line | 1.59 | 680 | R | 1999 |
| | To: 83-615 SOUTH | | | | |
| 640 83 | From: US 58 ALT | 2.46 | 1200 | R | 1999 |
| | To: 83-615 NORTH | | | | |
| 640 83 | From: 83-615 SOUTH | 0.84 | 860 | F | 2002 |
| | To: 83-1075 | | | | |
| 640 83 | From: 83-1075 | 0.27 | 400 | F | 2002 |
| | To: 83-1070 | | | | |
| 640 83 | From: 83-1070 | 0.14 | 330 | F | 2002 |
| | To: ECL Castlewood | | | | |
| 669 83 | From: ECL Castlewood | 0.40 | 60 | R | 09/19/2002 |
| | To: 83-683 | | | | |
| 682 83 | From: WCL Castlewood | 0.80 | 460 | N | 1999 |
| | To: SR 65 EAST | | | | |
| 682 83 | From: SR 65 EAST | 3.70 | 80 | R | 10/04/2002 |
| | To: SR 65 MID | | | | |
| 682 83 | From: SR 65 MID | 3.70 | 80 | R | 10/04/2002 |
| | To: SR 65 WEST | | | | |
| 683 83 | From: US 58 ALT WEST | 1.04 | 2500 | F | 2002 |
| | To: 83-787 | | | | |
| 683 83 | From: 83-787 | 0.04 | 1800 | F | 2002 |
| | To: 83-786 | | | | |
| 683 83 | From: 83-786 | 0.46 | 1700 | F | 2002 |
| | To: 83-695 | | | | |
| 683 83 | From: 83-695 | 0.36 | 420 | F | 2002 |
| | To: 83-615 | | | | |
| 683 83 | From: 83-615 | 0.36 | 490 | F | 2002 |
| | To: 83-669 | | | | |

| Route | Length | AADT | QA | Year | |
|---------------------------|----------------------|------|------|------|------------|
| Town of Castlewood | | | | | |
| 683 83 | From: 83-669 | 0.57 | 300 | F | 2002 |
| | To: SCL Castlewood | | | | |
| 694 83 | From: US 58 ALT | 1.73 | 220 | R | 1999 |
| | To: 83-615 | | | | |
| 695 83 | From: 83-683 | 0.12 | 1100 | R | 1999 |
| | To: 83-615 | | | | |
| 731 83 | From: SCL Castlewood | 0.61 | 40 | R | 10/04/2002 |
| | To: SCL Castlewood | | | | |
| 739 83 | From: SR 63 | 0.35 | 240 | R | 10/04/2002 |
| | To: 83-807 | | | | |
| 739 83 | From: 83-807 | 0.05 | 50 | R | 1999 |
| | To: 0.05 ME 83-807 | | | | |
| 739 83 | From: 0.05 ME 83-807 | 0.06 | 10 | R | 10/04/2002 |
| | To: Dead End | | | | |
| 748 83 | From: SR 65 | 0.14 | 70 | R | 10/04/2002 |
| | To: Dead End | | | | |
| 750 83 | From: 0.11 MW 83-615 | 0.11 | 40 | R | 10/04/2002 |
| | To: 83-615 | | | | |
| 750 83 | From: 83-615 | 0.10 | 70 | R | 10/04/2002 |
| | To: 0.10 ME 83-615 | | | | |
| 755 83 | From: SR 65 | 0.27 | 220 | R | 10/04/2002 |
| | To: End Loop | | | | |
| 762 83 | From: Dead End | 0.06 | 30 | R | 10/04/2002 |
| | To: SR 63 | | | | |
| 766 83 | From: Cul-de-Sac | 0.73 | 320 | R | 10/04/2002 |
| | To: US 58 ALT | | | | |
| 786 83 | From: 83-683 | 0.09 | 70 | R | 1992 |
| | To: 83-787 | | | | |
| 787 83 | From: 83-683 | 0.04 | 160 | R | 1986 |
| | To: 83-788 | | | | |
| 787 83 | From: 83-788 | 0.04 | 120 | R | 1986 |
| | To: 83-789 | | | | |
| 787 83 | From: 83-789 | 0.12 | 60 | R | 1986 |
| | To: 83-786 | | | | |
| 788 83 | From: 83-786 | 0.08 | 60 | R | 1986 |
| | To: 83-786 | | | | |
| 789 83 | From: Dead End | 0.05 | 70 | R | 1986 |
| | To: 83-787 | | | | |
| 807 83 | From: 83-739 | 0.20 | 80 | R | 10/04/2002 |
| | To: Dead End | | | | |

Virginia Department of Transportation
 Mobility Management Division
 2002
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Castlewood

| Route | Length | AADT | QA | Year |
|---------------------------|------------------|------|-----|--------------|
| Town of Castlewood | | | | |
| From: 809 83 | Dead End | 0.22 | 50 | R 10/04/2002 |
| To: 809 83 | 83-810 | 0.26 | 280 | R 1992 |
| From: 810 83 | US 58 ALT | 0.09 | 410 | R 10/04/2002 |
| To: 810 83 | 83-809 | | | |
| From: 811 83 | US 58 ALT SOUTH | 0.13 | 680 | R 10/04/2002 |
| To: 811 83 | 83-760 | | | |
| From: 813 83 | Dead End | 0.14 | 260 | R 10/04/2002 |
| To: 813 83 | SR 63 | | | |
| From: 828 83 | SR 65 | 0.32 | 90 | R 10/04/2002 |
| To: 828 83 | SR 65 | | | |
| From: 840 83 | Dead End | 0.20 | 120 | R 10/04/2002 |
| To: 840 83 | SR 65 | | | |
| From: 849 83 | Dead End | 0.08 | 30 | R 1992 |
| To: 849 83 | US 58 ALT | | | |
| From: 859 83 | 83-683 | 0.10 | 40 | R 1999 |
| To: 859 83 | Dead End | | | |
| From: 860 83 | Dead End | 0.62 | 830 | R 10/04/2002 |
| To: 860 83 | 83-683 | | | |
| From: 861 83 | Dead End | 0.45 | 190 | R 1999 |
| To: 861 83 | 83-860 | | | |
| From: 862 83 | 83-683 | 0.15 | 280 | R 1999 |
| To: 862 83 | Dead End | | | |
| From: 864 83 | 83-815 | 0.20 | 170 | R 1994 |
| To: 864 83 | 83-866 | | | |
| From: 865 83 | Dead End | 0.21 | 60 | R 1994 |
| To: 865 83 | 83-615 | | | |
| From: 866 83 | 83-864 | 0.20 | NA | |
| To: 866 83 | Dead End | | | |
| From: 868 83 | 83-615 | 0.06 | NA | |
| To: 868 83 | Dead End | | | |
| From: 900 83 | Dead End | 0.14 | NA | |
| To: 900 83 | 83-640 | | | |
| From: 1070 83 | Dead End | 0.05 | 140 | R 09/19/2002 |
| To: 1070 83 | 0.06 MN Dead End | | | |
| From: 1070 83 | 83-640 | 0.27 | 210 | R 09/19/2002 |

| Route | Length | AADT | QA | Year |
|---------------------------|----------------|------|------|--------------|
| Town of Castlewood | | | | |
| From: 1073 83 | Dead End | 0.05 | 30 | R 1999 |
| To: 1073 83 | 83-1070 | | | |
| From: 1074 83 | Begin Loop | 0.55 | NA | |
| To: 1074 83 | 83-640 | | | |
| From: 1075 83 | Dead End | 0.25 | 310 | R 09/19/2002 |
| To: 1075 83 | 83-640 | | | |
| From: 1078 83 | 83-1070 | 0.20 | 130 | R 1999 |
| To: 1078 83 | 83-1075 | | | |
| From: 9448 83 | Castlewood Sch | 0.20 | 2000 | R 1991 |
| To: 9448 83 | 83-683 | | | |
| From: 628 83 | SR 63 NORTH | 0.20 | 940 | R 1997 |
| To: 628 83 | NCL Castlewood | | | |