



Idea-66

Imagine the Possibilities

# I-66 INSIDE THE BELTWAY FEASIBILITY STUDY

---

Prepared for the  
Virginia Department of Transportation  
and  
Federal Highway Administration

MARCH 2005

# TABLE OF CONTENTS

---

<b>CHAPTER 1 – OVERVIEW .....</b>	<b>1-1</b>
1.1 PROJECT HISTORY .....	1-2
1.2 PROJECT TEAM .....	1-2
1.3 PUBLIC INPUT .....	1-2
1.4 PROBLEM STATEMENT .....	1-2
1.5 CONCEPTS .....	1-3
1.6 TECHNICAL ANALYSIS .....	1-3
1.7 RECOMMENDATIONS .....	1-3
<b>CHAPTER 2 – COMMUNITY OUTREACH ACTIVITIES .....</b>	<b>2-1</b>
2.1 PHASE I – PLAN DEVELOPMENT AND DATA GATHERING .....	2-1
2.1.1 Community Impact Assessment .....	2-1
2.1.2 Stakeholder Briefings .....	2-2
2.1.3 Toll-free INFO Line (1-866-816-4466) .....	2-3
2.1.4 Information Exchange .....	2-3
2.1.5 Project Web Site and E-mail: <a href="http://www.idea66.com">www.idea66.com</a> and <a href="mailto:info@idea66.com">info@idea66.com</a> .....	2-3
2.1.6 Community Involvement Plan Implementation .....	2-4
2.2 PHASE II – CONCEPTS DEVELOPMENT AND COMMUNITY INVOLVEMENT PLAN IMPLEMENTATION .....	2-4
2.2.1 Community Dialogues .....	2-4
2.2.2 Public Workshops .....	2-5
2.2.3 Open House .....	2-6
2.2.4 Community Presentations .....	2-6
2.2.5 Telephone Survey .....	2-6
2.2.6 Newsletters and Mailing List .....	2-7
2.2.7 Project Web Site and E-mail: <a href="http://www.idea66.com">www.idea66.com</a> and <a href="mailto:info@idea66.com">info@idea66.com</a> .....	2-7
2.2.8 Media Relations .....	2-8
2.2.9 Evaluation and Feedback .....	2-8
<b>CHAPTER 3 – ASSESSMENT OF THE CORRIDOR .....</b>	<b>3-1</b>
3.1 PHYSICAL CHARACTERISTICS OF THE CORRIDOR .....	3-1
3.1.1 Lane Configurations and Access Points .....	3-1
3.1.2 Geometric Deficiencies .....	3-2
3.1.3 Shoulder Conditions .....	3-2

3.2	HIGHWAY OPERATIONS IN THE CORRIDOR .....	3-2
3.2.1	Traffic Characteristics.....	3-2
3.2.2	Average Speeds.....	3-17
3.2.3	Travel Times.....	3-19
3.2.4	Origins and Destinations .....	3-19
3.3	TRANSIT OPERATIONS IN THE CORRIDOR.....	3-29
3.3.1	Transit Capacity .....	3-34
<b>CHAPTER 4 – PROBLEM STATEMENT.....</b>		<b>4-1</b>
<b>CHAPTER 5 – CONCEPTS.....</b>		<b>5-1</b>
5.1	NO-BUILD CONCEPT .....	5-1
5.2	HOV / HOT CONCEPTS.....	5-2
5.2.1	High Occupancy Vehicle (HOV) Lanes – Current Configuration .....	5-2
5.2.2	High Occupancy Vehicles (HOV) Lanes – Additional Lane.....	5-3
5.2.3	High Occupancy Toll (HOT) Lanes – Current Configuration .....	5-3
5.2.4	High Occupancy Toll (HOT) Lanes – Additional Lane.....	5-3
5.3	ROADWAY IMPROVEMENT CONCEPTS.....	5-3
5.3.1	Roadway Widening .....	5-3
5.3.2	Spot Improvements .....	5-7
5.4	TRANSIT CONCEPTS.....	5-8
5.4.1	Express Bus .....	5-9
5.4.2	Orange Line Reliever .....	5-10
5.4.3	Orange Line Improvements.....	5-13
5.4.4	Orange Line Additional Track / New River Crossing.....	5-13
5.4.5	New Metro Line .....	5-13
5.4.6	Bus Rapid Transit.....	5-15
<b>CHAPTER 6 – TECHNICAL EVALUATION .....</b>		<b>6-1</b>
6.1	EVALUATION CRITERIA OVERVIEW .....	6-1
6.2	MEASURES OF THE PROBLEM .....	6-3
6.2.1	Change in Volume-Capacity (V/C) Ratios.....	6-3
6.2.2	Change in Duration of Congestion .....	6-10
6.2.3	Change in Incident Occurrences.....	6-13
6.2.4	Change in Evacuation Potential .....	6-13
6.2.5	Presence of Continuous Shoulders.....	6-15
6.2.6	Change in Accessibility / Travel Time .....	6-16
6.3	MEASURES OF THE SOLUTION .....	6-18
6.3.1	Change in Mode Share Percentages .....	6-18
6.3.2	Change in Mode Share Numbers.....	6-20
6.3.3	Person Throughput on East West Roadways .....	6-21
6.3.4	Change in Vehicle Miles Traveled.....	6-21

6.3.5	Change in Total Daily Person Trips.....	6-22
6.3.6	Change in HOV / HOT Volumes.....	6-22
6.3.7	Network Connectivity Improvement.....	6-23
6.4	MEASURES OF COMMUNITY AND ENVIRONMENTAL IMPACT.....	6-23
6.4.1	Work Within Existing Right-of-Way .....	6-23
6.4.2	Utility Relocation.....	6-24
6.4.3	Retainage Walls and Noise Barrier Alterations .....	6-25
6.4.4	Existing Land Cover Converted and Visual Impacts .....	6-25
6.4.5	Water Resource Impacts .....	6-26
6.4.6	Presence of Sensitive Noise Receptors .....	6-26
6.4.7	Air Quality Impacts .....	6-26
6.4.8	Displacements/Acquisitions.....	6-27
6.4.9	Multi-use Trail, Public Land and/or Parkland Impacts .....	6-27
6.5	MEASURES OF EFFECTIVENESS .....	6-27
6.5.1	Capital Costs .....	6-28
6.5.2	Operating and Maintenance Costs.....	6-29
6.5.3	Design Exceptions Required to Stay within ROW .....	6-29
6.5.4	Ability to Maintain Bicycle Traffic.....	6-30
6.5.5	Ability to Maintain Traffic .....	6-31
6.5.6	Temporary Construction Impacts .....	6-31
6.6	MOST FEASIBLE CONCEPTS.....	6-31
<b>CHAPTER 7 – RECOMMENDED ACTIONS .....</b>		<b>7-1</b>

**APPENDIX A – STUDY ORGANIZATION CHART**

**APPENDIX B – I-66 CHRONOLOGY**

**APPENDIX C – CHANGES IN THE COLEMAN DECISION**

**APPENDIX D – CONGRESSMEN FRANK R. WOLF AND THOMAS M. DAVIS  
LETTER – JUNE 18, 2003**

**APPENDIX E – GOVERNOR MARK R. WARNER LETTER – SEPTEMBER 4, 2003**

**APPENDIX F – COMMISSIONER PHILIP A. SHUCET LETTER – MAY 10, 2004**

**APPENDIX G – PUBLIC COMMENTS**

**APPENDIX H – TELEPHONE SURVEY**

**APPENDIX I – CONCEPTS AND SOLUTIONS DISPLAY BOARDS**

**APPENDIX J – EXISTING RIGHT-OF-WAY**

**APPENDIX K – CROSS SECTIONS – LOCATIONS WITH RIGHT-OF-WAY  
CONSTRAINTS**

**APPENDIX L – LOCATIONS OF RIGHT-OF-WAY CONSTRAINTS**

## List of Figures

---

Figure 1-1.	Study Area .....	1-1
Figure 3-1.	Mainline Volumes.....	3-3
Figure 3-2.	Average Daily Weekday Ramp Volumes .....	3-4
Figure 3-3.	AM Peak Hour Ramp Volumes .....	3-5
Figure 3-4.	PM Peak Hour Ramp Volumes .....	3-5
Figure 3-5.	Changes in Daily Average Flow Rate for Dulles Connector On Ramp EB .....	3-6
Figure 3-6.	Changes in Daily Average Flow Rate for Westmoreland Street Off Ramp Eastbound.....	3-6
Figure 3-7.	Changes in Daily Average Flow Rate for Lee Highway (near East Falls Church) Off Ramp Westbound .....	3-7
Figure 3-8.	Changes in Daily Average Flow Rate for Sycamore Street On Ramp EB .....	3-7
Figure 3-9.	Changes in Daily Average Flow Rate for Fairfax Drive Off Ramp Eastbound .....	3-8
Figure 3-10.	Changes in Daily Average Flow Rate for Glebe Road On Ramp Eastbound .....	3-8
Figure 3-11.	Changes in Daily Average Flow Rate for Lee Highway (near Spout Run) Off Ramp Eastbound .....	3-9
Figure 3-12.	Changes in Daily Average Flow Rate for West Rosslyn Off Ramp Eastbound .....	3-9
Figure 3-13.	Changes in Daily Average Flow Rate for East Rosslyn On Ramp Eastbound .....	3-10
Figure 3-14.	Changes in Daily Average Flow Rate for East Rosslyn Off Ramp Westbound .....	3-10
Figure 3-15.	Changes in Daily Average Flow Rate for West Rosslyn On Ramp Westbound .....	3-11
Figure 3-16.	Changes in Daily Average Flow Rate for Lee Highway (near Spout Run) On Ramp Westbound .....	3-11
Figure 3-17.	Changes in Daily Average Flow Rate for Glebe Road Off Ramp Westbound .....	3-12
Figure 3-18.	Changes in Daily Average Flow Rate for Fairfax Drive On Ramp Westbound .....	3-12
Figure 3-19.	Changes in Daily Average Flow Rate for Sycamore Street Off Ramp WB .....	3-13
Figure 3-20.	Changes in Daily Average Flow Rate for Lee Highway (near East Falls Church) On Ramp Westbound .....	3-13
Figure 3-21.	Changes in Daily Average Flow Rate for Dulles Connector Off Ramp WB .....	3-14
Figure 3-22.	Summary of Collision History .....	3-15
Figure 3-23.	Westbound I-66 – Level of Service – AM Peak Period (Spring 1993, 1996, 1999, 2002) .....	3-16
Figure 3-24.	I-66 – Level of Service – AM Peak Period (Spring 2002) .....	3-17
Figure 3-25.	I-66 – Level of Service – PM Peak Period (Spring 2002) .....	3-18
Figure 3-26.	Average Speeds I-66 Westbound.....	3-19
Figure 3-27.	Site A: Westbound Mainline I-66 at Rosslyn Tunnel.....	3-20
Figure 3-28.	Site B: Westbound I-66 Entrance Ramp from Lee Highway (Rosslyn).....	3-21

Figure 3-29.	Site C: Westbound I-66 Entrance Ramp from Lee Highway (Spout Run) .....	3-21
Figure 3-30.	Site D: Westbound I-66 Entrance Ramp to Glebe Road (Ballston) .....	3-22
Figure 3-31.	Site E: Westbound I-66 Entrance Ramp from Fairfax Drive (Ballston) .....	3-22
Figure 3-32.	Site F: Westbound I-66 Exit Ramp to Sycamore Street (East Falls Church) ....	3-23
Figure 3-33.	Site G: Westbound I-66 Entrance Ramp from Washington Boulevard (East Falls Church) .....	3-23
Figure 3-34.	Site H: Westbound Mainline I-66 at Virginia Lane (Approaching I-495).....	3-24
Figure 3-35.	Site I1: Westbound Mainline Dulles Toll Road (Approaching I-495) .....	3-24
Figure 3-36.	Site I2: Westbound Dulles Airport Access Road (Approaching I-495).....	3-25
Figure 3-37.	Site J: Westbound I-66 Exit Ramp to I-495 Southbound .....	3-25
Figure 3-38.	Site K: Westbound VA-267 Exit Ramp to I-495 Northbound.....	3-26
Figure 3-39.	Matching Sites A and H: Westbound I-66 from Rosslyn Tunnel to Virginia Ln.	3-26
Figure 3-40.	Matching Sites A and I1: I-66 at Rosslyn Tunnel to VA-267 .....	3-27
Figure 3-41.	Matching Sites A and I2: I-66 at Rosslyn Tunnel to Dulles Airport Access Rd.	3-27
Figure 3-42.	Orange Line Metrorail AM Inbound Peak Hour Ridership and Passenger Capacity at Selected Locations Westbound .....	3-35
Figure 5-1.	Existing Typical Section .....	5-2
Figure 5-2.	Dedicated HOT Lane Typical Section.....	5-3
Figure 5-3.	Roadway Widening Typical Section.....	5-4
Figure 5-4.	Locations of Roadway Widening Options .....	5-5
Figure 5-5.	Example of Design Exception Use.....	5-7
Figure 5-6.	Spot Improvements at Fairfax Drive On-ramp .....	5-8
Figure 5-7.	Spot Improvements for Sycamore Street / Washington Blvd. Area .....	5-9
Figure 5-8.	Express Bus Typical Section .....	5-10
Figure 5-9.	Express Bus Option Location.....	5-11
Figure 5-10.	Additional Orange Line Track Typical Section .....	5-13
Figure 5-11.	Blue Line Extension .....	5-14
Figure 5-12.	BRT Typical Section .....	5-15
Figure 6-1.	Definition of Screenlines in the Study Corridor .....	6-4
Figure 6-2.	Change in AM Peak Period Eastbound Middle Screenline Link Volumes .....	6-6
Figure 6-3.	Change in PM Peak Period Westbound Middle Screenline Link Volumes .....	6-7
Figure 6-4.	Change in Daily Middle Screenline Link Volumes .....	6-9
Figure 6-5.	2030 Westbound AM Peak Period Middle Screenline V/C Ratio.....	6-10
Figure 6-6.	2030 Westbound PM Peak Period Middle Screenline V/C Ratio.....	6-11
Figure 6-7.	Westbound PM Peak Period VHT.....	6-12
Figure 6-8.	Change in PM Peak Period Westbound Auto Person Throughput .....	6-14
Figure 6-9.	Change in Daily Auto Person Throughput .....	6-14
Figure 6-10.	Change in Trip Origins of Users of I-66 Westbound AM Peak Period Direction	6-17
Figure 6-11.	Change in Trip Destinations of Users of I-66 Westbound AM Peak Period Direction.....	6-18
Figure 6-12.	Change in DC Core Person Trip Mode Shares.....	6-19
Figure 6-13.	Change in Arlington County Person Trip Mode Shares .....	6-19

Figure 6-14. Change in Fairfax County Person Trip Mode Shares .....	6-20
Figure 6-15. Summary Matrix.....	6-33
Figure 6-2a. Comparison of Concepts to 2030 CLRP.....	6-35
Figure 6-2b. Comparison of Concepts to 2030 CLRP.....	6-37
Figure 6-2c. Comparison of Concepts to 2030 CLRP.....	6-39

## List of Tables

---

Table 3-1.	Bus Service to Rosslyn Metrorail Station.....	3-30
Table 3-2.	Bus Service to West Falls Church Metrorail Station .....	3-31
Table 3-3.	Bus Service to Vienna Metrorail Station .....	3-33
Table 6-1.	Change in 2005 to 2030 Eastbound AM Peak Period Volumes .....	6-5
Table 6-2.	Change in 2005 to 2030 Westbound AM Peak Period Volumes .....	6-6
Table 6-3.	Change in 2005 to 2030 Westbound PM Peak Period Volumes .....	6-7
Table 6-4.	Change in 2005 to 2030 Daily Traffic Volumes Across the Middle Screenline ....	6-8
Table 6-5.	Change in AM Westbound VHT.....	6-11
Table 6-6.	Change in PM Westbound VHT.....	6-12
Table 6-7.	Change in Daily Westbound VHT .....	6-12
Table 6-8.	Change in Westbound One-Hour Person Capacity .....	6-15
Table 6-9.	Change in Transit Accessibility Compared with the 2030 No-Build .....	6-16
Table 6-10.	Origin of West bound AM Peak Period Users of I-66.....	6-16
Table 6-11.	Destination of Westbound AM Peak Period Users of I-66 .....	6-17
Table 6-12.	Change in Mode Share Numbers .....	6-21
Table 6-13.	Change in VMT .....	6-22