

Hydraulic Cement Concrete

2018 Bridge Construction Inspection School

Chaz Weaver, PE, PEM
VDOT Staunton District
Materials Engineer

2

How Important is Inspection?

According to the American Society of Civil Engineers*:

10% of issues are from design
10% are materials-related
10% are acts of God and
70% are workmanship!

3

Observer – Expectancy Effect

If you know I'm going to test, you'll make sure it's right

If you think I might test, you'll try to do it right

If you know I won't test, you'll just get it done

4

History of Concrete

300 BC – Romans used pozzualana, found near Pozzouli (near Naples, Italy)

1756 – John Smeaton, British engineer, rediscovers hydraulic cement from testing mortar

1824 – Joseph Aldin, bricklayer and mason in Leeds, England, patented Portland cement – named after the stone quarried on Isle of Portland off Britain's coast

1871 – 1st US Portland cement plant at Coplay, PA

1889 – 1st reinforced concrete bridge built

1891 – 1st US concrete street at Bellefontaine, OH

5

History of Concrete

- 1913** – 1st Ready-Mix concrete
- 1916** – Portland Cement Association founded
- 1917** – ASTM standard for concrete
- 1936** – Hoover Dam completed
- 1940** – Air-entrained concrete
- 1970** – Fiber-reinforced concrete
- 1970s** – Silica Fume used in concrete
- 1986** – Concept for self-consolidating concrete
- 1990s** – Low-permeability concrete studies

6

Characteristics of Concrete

- Strength**
- Set time and strength gain**
- Permeability**
- Workability**
- Durability**

- Fracture Toughness**
- Creep**
- Fatigue Behavior**

7

Types of Concrete

Self-Consolidating Concrete (SCC)

Lightweight Concrete

Low Shrinkage Concrete

Ultra-High Performance Concrete (UHPC)

8

Concrete Constituents

Cement – Calcium, Silica, Alumina and Ferrite

Typically Type I/II – Most common

Type III – Higher early strength

Type IV – Mass concrete (lower heat of hydration)

Type V – High sulfate resistance

Blended – IS, IP, IT, IL

Aggregates – Well-graded

Lower cement content

Lower water demand

Reduce drying shrinkage

Concrete Constituents

Admixtures

Air-Entrainment

Water-Reducing (Plasticizers)

Retarder

Accelerator

Corrosion Inhibitor

Pozzolans

- Fly Ash: residue from coal-burning plants
- Ground Granulated Blast Furnace Slag: top of furnace ladle
- Silica Fume: solidified silicon dioxide vapor
- Reduce permeability
- Reduce ASR
- Reduce Sulfate Attack

Durability

Freeze-Thaw

Improper Handling

Air-Entrainment

poor cold weather placement



Alkali-Silica Reaction (ASR)

PCC contains N_2O and K_2O , which react with silica in the aggregate to form silica gel. This gel aggressively absorbs water, which causes the pressure that causes cracking

Low alkali cements

11


Concrete Scaling



What causes this?


12

Concrete Scaling



13

Concrete Scaling



14

Durability

Sulfate Attack

C_3A reacts with sulfate ions, creating ettringite crystals that expand and cause cracking, OR
 CH_2 crystals turn to gypsum (lower strength)

Low Permeability Concrete

Corrosion of Steel

Water causes steel to rust, which expands it – volume increase cracks concrete, allowing more water intrusion

Low Permeability Concrete/ CRR Steel

Shrinkage

Drying Shrinkage

Water not needed for hydration evaporates

- Should take 90+ days **Don't add water at site**
- Total water, not water/cement ratio

Effect of W/C Ratio on Drying Shrinkage

- Drying shrinkage is difficult to eliminate, but is relatively easy to control by lowering the amount of total water in the mix

Cement Content and Drying Shrinkage*			
Cement Content, bags/cu yd.	Water Content, cu yd.	Water-Cement Ratio	Shrinkage, %
5	0.20	0.72	0.03
6	0.21	0.62	0.03
7	0.21	0.54	0.03
8	0.21	0.46	0.03

* 3x3x10-in. prisms cured wet 7 days, dried 14 days

i Total water, not w/c ratio, is important in controlling drying shrinkage

U.S. Department of Transportation Federal Highway Administration | MODULE 6 LESSON 3 | THE ROLE OF CEMENT AND WATER IN PLASTIC AND HARDENED PCC | Resources: Highway Help

Photo: FHWA

Shrinkage

Plastic Shrinkage

Evaporation rate (humidity, air temperature, concrete temperature and wind velocity)



**Cover quickly;
Fogging is not
intended to dampen
surface!**

Photo: FHWA

Shrinkage

Early Age Tensile Strength




Photo: FHWA

Shrinkage

Shrinkage Stress Vs. Strength




Photo: FHWA

Shrinkage




Photo: FHWA

Cracking = High Permeability



Photos: VDOT

VDOT Concrete

Approved Plant

Approved Job Mix Formula *for that application*

- **Low-Shrinkage, Low Permeability, Lightweight, Non-Polishing, Self-Consolidating, etc.**
- **Include JMF number with C-25 Source of Materials**
- **Why wait?**
 - Strength/Permeability/Shrinkage tests take 28 days!
 - Should be discussed at Pre-Construction Meeting

VDOT Concrete

Trucks

- **Self-Inspection**
- **Check anyway**
- **Any signs of contamination, clumping, etc. – reject load!**

Concrete – Planning

- **Delivery Rate (number of trucks)**
 - **Haul time**
 - **Additional concrete is typically necessary**
 - Stay-in-Place forms
 - Crown/overhangs
 - Rejected loads
 - Poor yield
- **Method of Placement (pump?)**
- **Backup Plan – Placement and Curing**
 - **Equipment Breakdown**
 - Spare Parts?
 - **Cold Joints**
 - **Materials must be on-site!**

Concrete – Planning

- **Weather – Hot or Cold**
 - **Have an acceptable plan!**
 - **Cannot simply blow hot air (evaporation)**
- **Location for testing**
 - **Safe but efficient**
- **Location for cylinder curing box**
 - **Continuous Recording Thermometer**

Concrete – Temperature

Temperature requirements are written in stone.

- No legal thing as “at contractor’s risk” on VDOT project!

Minimum 40° F for all concrete

- Bridge Deck curing – minimum 50° F for 72 hours, then minimum 40° F for duration of curing period
- 2016 R&B Specs Section 404.03(I) for protection of concrete

Concrete – Temperature

Different applications have different maximum temperatures

- Incidental Items – 95° F
- Paving – 95° F
- Bridge Decks – 85° F
- Retaining Walls and Other – 90° F

Concrete – Temperature




Photo: FHWA

Concrete – Temperature

Cold Weather

- Mix water heated / Aggregate heated
- Accelerator to help hydration
- NO FREEZING.

Hot Weather

- Mix water cooled / Aggregate misted / Ice chips
- Retarder to slow hydration

Concrete – Re-tempering

As temperature rises, air entrainment and slump suffer

- **Air-entraining admixture can be added on-site**
- **Water reducer (plasticizer) can be added to increase slump**
 - **In lieu of adding water! Water decreases strength**
 - **Superplasticizer increases slump without reducing strength**

Re-tempering requires thorough mixing!

- **70 revolutions; 14-20 revolutions/minute**

Admixtures should not be added together!

Concrete – Inspection

VDOT materials certification is required

Are you checking the tickets?

- **Don't rely on the plant to do this for you!**
- **Batch weights should be included**
- **Should closely match TL-28**

Concrete – Testing

Are you testing each load?

- OK if mix delivered is consistent
 - Unit Weight
 - Air Entrainment
 - Slump
 - Temperature
- If there is any reason to suspect an issue, test it!
 - Penalties can only be applied to loads tested
 - Trust, but verify
 - Make additional cylinders
 - Document where each load went

Concrete – Placement

Pumping

Horizontal discharge should be used at the end

- Limits segregation and loss of entrained air

Bucket

Minimal impact on properties

Belts

Minimal impact on properties

Direct Discharge

Segregation increases as slump increases

Air-entrainment OK as long as drop height minimal

Tremie

Air-entrainment can be reduced

Segregation can be reduced by controlling drop height





Concrete – Placement

Proper vibration means:

- **Vertical** insertion of the vibrator;
- In the case of wet on wet lifts, the vibrator should penetrate the existing lift;
- Not using the vibrator to move or drag the concrete horizontally;
- Positioning the vibrator so the zone of influence of the vibrator insertions overlap;
- Not contacting any embedded steel; and
- Vibrating only long enough for uniform consolidation (usually 5 to 15 seconds)



Concrete – Placement



Photos: FHWA

Concrete – Curing

Various methods are allowed, but curing must begin directly after finishing

Proper curing improves:

- Strength
- Permeability
- Durability

Deck Overlays

Surface Preparation



Photos: VDOT

37

More Training

**TC3 Courses
(VDOTU and AASHTO)**

**Bridge Inspection Safety
Plan Reading – Bridge Plans
Drilled Shaft Inspection Tutorial
Construction of MSE Walls
Self-Consolidated Concrete
Concrete Series**

38

Thanks!

Questions?

**Chaz Weaver, PE, PEM
540.746.8801
chaz.weaver@vdot.virginia.gov**